

CODE:	8041
--------------	-------------

PRODUCT:	PVC WHITE GLOSSY 0.08 / AP120 / CH120
-----------------	--

SET	DESCRIPTION						
	Monomeric calandered glossy white PVC film, self-adhesive suitable for designs, conventional and UV screen printing, advertisements, decorations, signalling and electronic cutting (plotter). Suitable for printing with solvent-based ink.						
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>245 ± 17</td> </tr> <tr> <td>THICKNESS</td> <td>µm</td> <td>212 ± 18</td> </tr> </table>	GRAMMAGE	g/ m ²	245 ± 17	THICKNESS	µm	212 ± 18
GRAMMAGE	g/ m ²	245 ± 17					
THICKNESS	µm	212 ± 18					

FRONT	DESCRIPTION						
PVC GLOSSY WHITE	Monomeric calandered glossy white PVC film, mainly used for electronic cutting (plotter).						
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>105 ± 10</td> </tr> <tr> <td>THICKNESS</td> <td>µm</td> <td>80 ± 10</td> </tr> </table>	GRAMMAGE	g/ m ²	105 ± 10	THICKNESS	µm	80 ± 10
GRAMMAGE	g/ m ²	105 ± 10					
THICKNESS	µm	80 ± 10					

ADHESIVE	DESCRIPTION															
AP120	<p>Permanent acrylic adhesive in aqueous emulsion. It has good initial adhesiveness and great final adhesiveness. It can be used on various types of substrates, such as glass, paper, metal surfaces, packaging and plastic parts.</p> <p>We do not recommend using this adhesive on hard-to-stick substrates such as textured, uneven or porous surfaces and surfaces with non-stick properties.</p>															
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>20 ± 2</td> </tr> <tr> <td>TACK</td> <td>g/25mm</td> <td>Minimum 550</td> </tr> <tr> <td>ADHESIVENESS</td> <td>g/25mm</td> <td>Minimum 900</td> </tr> <tr> <td>TEMP. OF APPLICATION</td> <td>° C</td> <td>+ 10</td> </tr> <tr> <td>RESIST. TO TEMPERATURE</td> <td>° C</td> <td>-10 to +70</td> </tr> </table>	GRAMMAGE	g/ m ²	20 ± 2	TACK	g/25mm	Minimum 550	ADHESIVENESS	g/25mm	Minimum 900	TEMP. OF APPLICATION	° C	+ 10	RESIST. TO TEMPERATURE	° C	-10 to +70
GRAMMAGE	g/ m ²	20 ± 2														
TACK	g/25mm	Minimum 550														
ADHESIVENESS	g/25mm	Minimum 900														
TEMP. OF APPLICATION	° C	+ 10														
RESIST. TO TEMPERATURE	° C	-10 to +70														

LINER	DESCRIPTION						
CH120	Special couche paper with a siliconized face, recommended for projects requiring excellent dimensional stability.						
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>120 ± 5</td> </tr> <tr> <td>THICKNESS</td> <td>µm</td> <td>112 ± 5</td> </tr> </table>	GRAMMAGE	g/ m ²	120 ± 5	THICKNESS	µm	112 ± 5
GRAMMAGE	g/ m ²	120 ± 5					
THICKNESS	µm	112 ± 5					

STOCK WARRANTY: This product has a warranty of 01 year as long as it remains stored in its original packaging, conditioned at a temperature of 23 ± 2°C and relative humidity of 65 ± 10%.

ATTENTION: All of the above information regarding **PROTACK** products is for guidance only. We recommend adapting the indications on the use of our products to local conditions, taking into account the materials and/or substrates to be used. If you have questions as to the application, contact our Technical Department. We reserve the right to make improvements and modifications to these products without prior notice.